



	CODICE	R	L	L1	ød1	Bta	L	ød
NEW	4634-005-010	0,25	1	-	-	15°	40	3
NEW	4634-005-040	0,25	1	4	0,44	15°	40	3
NEW	4634-005-070	0,25	1	7	0,44	15°	40	3
NEW	4634-005-100	0,25	1	10	0,44	15°	40	3
NEW	4634-006-010	0,3	1	-	-	15°	40	3
NEW	4634-006-050	0,3	1	5	0,54	15°	40	3
NEW	4634-006-080	0,3	1	8	0,54	15°	40	3
NEW	4634-006-120	0,3	1	12	0,54	15°	40	3
NEW	4634-008-020	0,4	2	-	-	15°	40	3
NEW	4634-008-070	0,4	2	7	0,73	15°	40	3
NEW	4634-008-100	0,4	2	10	0,73	15°	40	3
NEW	4634-008-150	0,4	2	15	0,73	15°	40	3
NEW	4634-010-020	0,5	2	-	-	15°	50	3
NEW	4634-010-060	0,5	2	6	0,92	15°	50	3
NEW	4634-010-080	0,5	2	8	0,92	15°	50	3
NEW	4634-010-100	0,5	2	10	0,92	15°	50	3
NEW	4634-010-120	0,5	2	12	0,92	15°	50	3
NEW	4634-010-140	0,5	2	14	0,92	15°	50	3
NEW	4634-010-160	0,5	2	16	0,92	15°	50	3
NEW	4634-010-200	0,5	2	20	0,92	15°	50	3
NEW	4634-010-250	0,5	2	25	0,92	15°	50	3
NEW	4634-015-060	0,75	3	6	1,42	15°	50	3
NEW	4634-015-080	0,75	3	8	1,42	15°	50	3
NEW	4634-015-100	0,75	3	10	1,42	15°	50	3
NEW	4634-015-120	0,75	3	12	1,42	15°	50	3
NEW	4634-015-140	0,75	3	14	1,42	15°	50	3
NEW	4634-015-160	0,75	3	16	1,42	15°	50	3
NEW	4634-015-200	0,75	3	20	1,42	15°	50	3
NEW	4634-015-250	0,75	3	25	1,42	15°	50	3
	4634-020-060	1	6	-	-	15°	50	3
	4634-020-100	1	6	10	1,92	15°	50	3
NEW	4634-020-120	1	6	12	1,92	15°	50	3
NEW	4634-020-140	1	6	14	1,92	15°	50	3
	4634-020-160	1	6	16	1,92	15°	50	3
	4634-020-200	1	6	20	1,92	15°	50	3
	4634-020-250	1	6	25	1,92	15°	50	3

CODICE	R	L	l1	od1	Bta	L	od
4634-030-150	1,5	9	15	2,8	-	75	3
4634-040-200-S	2	15	20	3,8	-	75	4
4634-040-200-N	2	15	20	3,8	-	100	4
4634-060-250-S	3	20	25	5,7	-	60	6
4634-060-250-N	3	20	25	5,7	-	100	6
4634-060-250-L	3	20	25	5,7	-	150	6
4634-080-350-N	4	25	35	7,7	-	100	8
4634-080-350-L	4	25	35	7,7	-	150	8
4634-100-350-N	5	25	35	9,9	-	100	10
4634-100-350-L	5	25	35	9,9	-	150	10
4634-120-350-N	6	25	35	11,7	-	100	12
4634-120-350-L	6	25	35	11,7	-	150	12